



LG Stylo 3 Plus Rear Camera Replacement

How to replace a LG Stylo 3 Plus rear camera.

Written By: Patricia Pires Dias



INTRODUCTION

Is the rear camera on your LG Stylo 3 Plus no longer taking great photos? Removing the rear camera for cleaning or replacement may sound daunting, but it only takes about 5 minutes and some simple tools. Follow this guide to quickly replace your rear camera and continue taking great pictures!

TOOLS:

- [iFixit Opening Tools](#) (1)
 - [Phillips #000 Screwdriver](#) (1)
 - [Tweezers](#) (1)
-

Step 1 — Back Cover



- i** Power off the phone before beginning disassembly.
- Place the phone face down.
 - Insert a fingernail or a plastic opening tool into the gap on the side of the phone.
 - Carefully slide your finger or the tool throughout the edge of the phone to ease the back case off.

Step 2 — Battery



- Place the back cover off to the side.
- Insert the opening tool into the small gap below the battery.
- Carefully pop the battery out to prevent damage.

Step 3 — Rear Camera



- Remove the twelve 4mm screws using the Phillips #000 screwdriver.
- Use the plastic opening tool to remove the inner case.
- Carefully remove the inner case.

Step 4



- Use your fingernail or the plastic opening tool to flip the flex cable.
- Use the precision tweezers to carefully grasp and pull out the camera.

To reassemble your device, follow these instructions in reverse order.

This document was generated on 2020-11-28 07:09:16 AM (MST).

