



Compaq Mini 110 Keyboard Replacement

Sticky keys? Simply just want to get rid of...

Written By: alea



INTRODUCTION

Sticky keys? Simply just want to get rid of your keyboard? Here's how.

TOOLS:

- [Spudger](#) (1)
 - [Phillips #0 Screwdriver](#) (1)
-

Step 1 — Battery



- Locate the battery and the battery tabs on the bottom of the Compaq Mini.

Step 2




- Push both tabs inward simultaneously and slide the battery out.

Step 3 — RAM



- Use a Philips #0 screwdriver to unscrew the two screws covering the memory compartment on the bottom of the laptop and remove the cover.

Step 4



- Push out the side tabs simultaneously and pull out the old RAM module.
- ★ When inserting a new RAM stick, be sure to evenly insert the gold pins in the same orientation that the old module was removed. While sliding the module in, press the side tabs in place.


Step 5 — Keyboard



- Remove the rubber pads located on the corners of your Compaq Mini.

⚠ There may be junk underneath it. This is residue left from the glue that held on the rubber pad. Just scrape it away to find the screw.

Step 6



- Unscrew all the corner screws. There are four total, one under each rubber pad.

Step 7



- Unscrew the screw for the bottom case located in the RAM compartment.

Step 8



- Remove the three screws in the silver tabs at the back of the keyboard.
- ⓘ These are located at the back of the base under the screen.
- Lift the keyboard away from the laptop.

To reassemble your device, follow these instructions in reverse order.