



Huawei Honor 8 Screen Replacement

Huawei Honor 8 LCD + Touch Screen Replacement

Written By: Nihoul Victor





TOOLS:

- [iSesamo Opening Tool](#) (1)
- [Tornevis Cruciforme PH1](#) (1)
- [New Item](#) (1)



PARTS:

- [New Item](#) (1)

Step 1 — Remove the back casing



- Heat the parts marked in red on the back side of the phone with a hair dryer or heat gun.
- Attention: The sides have to be hot, not scalding.
- Insert the iSesamo delicatley between the two sides (see photo)
- Once the iSesamo is inserted, slide it along the sides to remove the adhesive.
- ATTENTION: DO NOT SLIDE THE ISESEMO ALONG THE PART MARKED IN GREEN.

Step 2 — Disconnect the rear window



- Remove the screw on the metal plate which protects the fingerprint sensor cable
- Remove the the fingerprint censored cable using a plastic spudger.

Step 3 — Remove the protection from the motherboard



- Remove the 16 screws with a Phillips screwdriver.
- Using the iSesamo, remove the protection from the motherboard

Step 4 — Take off the battery




- Remove the 2 tabs marked in red.
- Gently remove the battery with a playing card or bank card.

Step 5 — Prepare to take off the screen



- Peel off the connector on the screen.
- Heat the contours of the screen as shown in Step 1.

Step 6 — Take off the screen



- insert the iSesamo between the screen and the chassis
- Be sure to pass the iSesamo under the white plate of the screen (see photo)
- Go around the phone.
- Note that the operation can be more complicated depending on the level of the screen.

Step 7 — Clean the frame



- Carefully remove the pieces of glass and the adhesive on the frame

Step 8 — Paste the new screen



- Glue the screen on the frame by passing the sheet through the hole provided for this purpose

To reassemble your device, follow the instructions in reverse order :)