




LG Xenon Microphone Replacement

If you need to repair or replace the...

Written By: Katy Conlin



INTRODUCTION

If you need to repair or replace the microphone, this is the guide you need!



TOOLS:

- [Phillips #00 Screwdriver](#) (1)
 - [iFixit Opening Tool](#) (1)
-

Step 1 — Back Case



- Turn the phone over so the back side is facing you.

Step 2



- Placing your thumb on the bottom of the phone, apply pressure to the small ridge in the middle of the phone and push upward towards the camera.
- The back casing should slide off.

Step 3 — Battery




- Using your index finger, pull the top of the battery out first. Place your finger at the top center of the battery in the gap that is provided. Then pull the battery towards yourself.
- The battery should easily fall out after the top of the battery has been pulled out.

Step 4 — Motherboard





- Unscrew the six 2.4mm Phillips #00 screws (three on the left and three on the right of the phone) to remove the inner back case.

Step 5




- Once all six screws are removed, use the plastic opening tool to carefully pry apart the inner back case. Push the plastic tool underneath the case. Carefully push upward, with the tool, while moving it around the case.

Step 6




- Remove the camera, lock, and volume buttons from the side of the phone.

Step 7



- Carefully remove the two 3mm Phillips #00 screws (one on the top and one on the bottom) that are attaching the motherboard to the phone.

Step 8





- For this next step, carefully lift and remove the motherboard.
 - A connector cable will still be connected to the motherboard upon removing it.

⚠ Damage to the connector cable will permanently disable phone.


This document was generated on 2023-04-03 09:23:37 AM (MST).

Step 9





- Carefully unclip the silver metallic tab from the motherboard.

Step 10



- Once the cable is removed, you have successfully disassembled the motherboard of your phone.

Step 11 — Microphone



- The microphone is located on the bottom corner of the motherboard.
- ⚠ Take caution when repairing the microphone to not damage the motherboard.

To reassemble your device, follow these instructions in reverse order.